

Read Me First

Step-by-Step Preparation and Set Up for your GW-VAM Controller

Pre-Installation Instructions for the MotoChello GW-VAM unit

1	Select the Gold Wing Intercom and set the level to 6. <i>(this will be much lower than where it is usually set)</i>
2	Remove the standard Gold Wing 6-pin connector <i>(under the left glove box)</i>
3	 IMPORTANT: Old contacts will be dirty and can cause a poor connection , effecting performance. Clean them with contact cleaner before inserting the VAM connector. <u>Do not skip this step!</u>
4	After cleaning, plug the VAM unit into the red rectangular connector on your Gold Wing.
5	Connect Accessory Power to the red wire on the VAM unit using the supplied Posi-Tap. <i>(See instructions)</i>
6	Turn the sensitivity knob on the VAM unit fully counterclockwise to turn on the microphone
7	Start Gold Wing and adjust intercom volume until it is at a comfortable level.
8	Adjust microphone knob on VAM unit until the microphone shuts off when you are not talking (about 1/2 way)
9	Turn on music source and set to a comfortable level
10	<p>If wind noise activates the microphone, turn the knob a little more clockwise (HIGH / less sensitive)</p> <p>If you have to talk too loud to activate the microphone, turn the knob counterclockwise a little at a time until microphone activates with your voice (LOW / more sensitive)</p>

